ASISSLB5

AS-Interface - for Ø 22 emergency stop - plastic

Product availability: Non-Stock - Not normally stocked in distribution facility



Main			
Commercial Status	End of commercialisation		
Product or component type	Interface for Ø 22 emergency stop		
Range compatibility	AS-Interface cabling system		
Fixing collar material	Plastic		
AS-i profile	0.B.F.F		
Supply	Via AS-Interface		

Complementary

Contacts type and composition	1 NC + 1 NC	
Addressing	Using adjustment terminal	
[Us] rated supply voltage	24 V DC (- 1515 %)	
Power consumption	1.2 W	
Current consumption	45 mA AS-Interface line	
Connections - terminals	IDC AS-Interface line	
Mechanical durability	300000 cycles	
Product weight	0.09 lb(US) (0.04 kg)	

Environment

Standards	EN 954-1 category 4	
	EN/IEC 60204-1	
	EN/IEC 60947-5-1	
	ISO 13849-1 category 4	
Product certifications	CSA	
	TÜV	
	UL	
IP degree of protection	IP20 conforming to IEC 60529	
Ambient air temperature for operation	14131 °F (-1055 °C)	
Ambient air temperature for storage	-13185 °F (-2585 °C)	
Shock resistance	10 gn	
Vibration resistance	5 gn	

Ordering and shipping details

Category	18340 - AS-I SAFE PRODUCTS (SPX2)	
Discount Schedule	SPX2	
GTIN	00785901437895	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	FR	

Warranty period

18 months