# Product data sheet Characteristics

## MPZ15S40FSS Mini Power Zone 15kVA 480-120/240

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 14758.00 USD

Commercial Status	Commercialised
Product or component type	Sealed Transformer
Product certifications	UL listed
Range of product	Mini Power-Zone
Box number	В
Insulation temperature	365 °F (185 °C)
Phase	1 phase
Primary voltage	480 V
Secondary voltage	120/240 V
Number of tap-offs	2 5 % FCBN
Rated power in VA	15 kVA
Temperature rise	115 °C
Material	Copper
Short-circuit current	18 kA
Circuit breaker application	Feeder breaker Secondary main breaker Primary main breaker
Board name	QO Load Center interior
Number of spaces	24
Number of circuits	24
NEMA degree of protection	NEMA 3R stainless steel 316

### Ordering and shipping details

Category	16275 - MPZ PLUG ON BRANCH CB	
Discount Schedule	PE2	
GTIN	00785901457701	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	US	

#### Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be Compliant on 3Q2014	
REACh	Reference not containing SVHC above the threshold	

#### Contractual warranty

· · · · · · · · · · · · · · · · · · ·				
Warranty period	18 months			