

Product availability: Stock - Normally stocked in distribution facility

Main

Commercial Status	End of commercialisation
Range of product	Modicon Momentum automation platform
Product or component type	M1/M1E processor adaptor
Concept	Transparent Ready
Level or class	Class B10
Software designation	ProWORX 32 ProWORX NxT V2.0 Modsoft >= V2.5 Concept V2.6
Communication port protocol	Ethernet
Processor name	X 86 based (INTEL, AMD) IEC executive
Clock frequency	50 MHz

Complementary

Web services	Data editor Rack viewer Web page loader Web page loader software tool
Ethernet service	I/O scanning Modbus TCP messaging
Discrete I/O processor capacity	8192 I/8192 O
Memory type	RAM 544 kB Flash 1 MB
Memory description	Data 24 kB Program memory 200 kB IEC Program memory 18 kB LL984
Material	Lexan
Word length	16 bit
[Us] rated supply voltage	5.0 V DC +/-5 %
Supply	By Momentum I/O base
Exact time for 1 K instruction	1 ms
Register I/O processor capacity	26048 I/26048 O
I/O limit processor capacity	8192 bits max
I/O words/drop	80 I/O ProWORX 128 I/O Concept
Number of port	1 Ethernet 1 I/O bus
Marking	CE
Product weight	0.09 lb(US) (0.042 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Protective treatment	TC
Ambient air temperature for operation	32...140 °F (0...60 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Relative humidity	5...96 % without condensation
Operating altitude	6561.68 ft (2000 m)
Shock resistance	<= 15 gn peak (duration = 11 ms) half sine wave acceleration
Vibration resistance	0.75 mm d.a 1 gn
Product certifications	CUL FM Class 1 Division 2 Nema type 250 UL

Ordering and shipping details

Category	18206 - MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	00785901396376
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be Compliant on 4Q2013
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------