Product data sheet Characteristics

XAPJ1501

die-cast empty control station - XAPJ - \emptyset 22 - zinc alloy - 1 opening

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 136.00 USD



Main					
Commercial Status	Commercialised				
Range of product	Harmony XAP				
Product or component type	Die-cast empty control station				
Device short name	XAPJ				
Product destination	For Ø 22 mm control and signalling units				
Product front plate size	80 x 80 mm				
Usable depth	2.93 in (74.5 mm)				
Number of cut-out	1 cut-out				
Colour of base of enclosure	Blue				
Colour of cover	Yellow				
Material	Zinc alloy				
Cable entry	1 hole without blanking plug for cable gland <= 0.55 in (14 mm) 1 hole with blanking plug for cable gland <= 0.55 in (14 mm)				
Product mounting	Flush mounting				
IP degree of protection	IP657 conforming to NF C 20-010 IP65 conforming to IEC 60529				

Complementary

Number of vertical rows	1
Product weight	1.33 lb(US) (0.605 kg)

Environment

Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Class of protection against electric shock	Class I conforming to NF C 20-030 Class I conforming to IEC 60536

Ordering and shipping details

22475 - WALL STATIONS	
CS2	
00785901409144	
1	
Non-Stock - Not normally stocked in distribution facility	
N	
MA	
	CS2 00785901409144 1 Non-Stock - Not normally stocked in distribution facility N

Contractual warranty


Warranty period	18 months

Product data sheet **Dimensions Drawings**

XAPJ1501

Dimensions and Fixing

Refer to the product characteristics to get the number of cut-outs.



- 1 hole, without blanking plug, for cable gland with 14 mm/0.55 in. maximum clamping capacity
- 1 hole, with blanking plug (protrusion 6 mm/0.23 in.), for cable gland with 14 mm/0.55 in. maximum clamping capacity $2 \times \emptyset$ 5.6 mm/0.22 in. holes, depth 20 mm/0.78 in.
- (2) (3) P
- Usable depth

а		b		С		G		Н		Р	
mm	in.	mm	in.								
80	3.15	80	3.15	77	3.03	50	1.97	65	2.56	74.5	2.93