

## Product data sheet

### Characteristics

# HOM816M200FTRB

## LD CTR HOM MB FT 240V 200A 1PH 8SP NEMA3



Product availability: Stock - Normally stocked in distribution facility



### Main

Commercial Status	End of commercialisation
Product or component type	Load Centre
Range of product	Homeline
Load centre type	Main breaker
Line Rated Current	200 A
Number of spaces	8
Short-circuit current	22 kA
Number of circuits	16
Number of tandem circuit breakers	8
Phase	1 phase
System Voltage	120/240 V AC

### Complementary

AWG gauge	AWG 4...250 kcmil (copper) AWG 4...250 kcmil (aluminium)
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Feed-thru lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded galvanized steel
Cover finish	Gray baked enamel
Product certifications	UL listed file:E-6294

### Ordering and shipping details

Category	00149 - HOM 2-8 CKT,MLO,NEMA1&3R
Discount Schedule	DE3C
GTIN	00785901076544
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1411 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	Lifetime
-----------------	----------