# Product data sheet Characteristics

## HOM12M200RB LOADCTR HOM MB 240V 200A 1PH 12SP NEMA3R



Product availability: Stock - Normally stocked in distribution facility

B 4		
N /I		n
IVI	$\boldsymbol{\sigma}$	

Midiri	
Commercial Status	End of commercialisation
Product or component	Load Centre
type	
Range of product	Homeline
Load centre type	Main breaker
Line Rated Current	200 A
Number of spaces	12
Short-circuit current	22 kA
Number of circuits	12
Number of tandem circuit breakers	0
Phase	1 phase
System Voltage	120/240 V AC

#### Complementary

AWG gauge	AWG 4250 kcmil (copper) AWG 4250 kcmil (aluminium)
NEMA degree of protection	NEMA 3R outdoor
Cover type	Surface cover
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded galvannealed steel
Cover finish	Gray baked enamel
Product certifications	UL listed file:E-6294

#### Ordering and shipping details

Category	00145 - HOM LC&CVR,12-42CKT NEMA3R	
Discount Schedule	DE3C	
GTIN	00785901409014	
Nbr. of units in pkg.	1	
Product availability	Stock - Normally stocked in distribution facility	
Returnability	Υ	
Country of origin	US	

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1411 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

### Contractual warranty

Warranty period	Lifetime