Product data sheet Characteristics

2510KG6B MANUAL SWITCH 600VAC K+OPTIONS

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 233.00 USD

	2	
Commercial Status	Commercialised	
Product or component type	Single Unit Manual Switch	
Range of product	К	
Line Rated Current	30 A	
Product certifications	CE CSA UL listed	
Cable entry	0.5" and 0.75" knock-outs (top and bottom)	
NEMA degree of protection	NEMA 1 painted sheet steel standard size	
Motor power hp	20 hp 575 V AC 15 hp 460 V AC 7.5 hp 230 V AC 1.5 hp 230 V DC 2 hp 115 V DC 1 hp 90 V DC 2 hp 115 V AC	
System Voltage	230 V DC 600 V AC	
Poles description	3P	
Control type	Toggle	
Phase	3 phases	
Local signalling	Red indicator 208277 V	
Motor starter type	Non reversing	
Electrical connection	Screw clamp terminals	

Ordering and shipping details

Category	21102 - 2510,2511,2512 K	
Discount Schedule	CP1	
GTIN	00785901005957	
Nbr. of units in pkg.	1	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be Compliant on 3Q2014	
REACh	Reference not containing SVHC above the threshold	

Contractual warranty

Warranty period	18 months