Product data sheet Characteristics

8536SBG2V81CF4P1T

Non-Reversing Starter Size 0, 3-Pole, Thermal - Melting Alloy

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1601.00 USD

	٠		٠	
N	/1	2	п	r

· · · · · · · · · · · · · · · · · · ·	
Commercial Status	Commercialised
Product or component type	Starter
Range of product	S
Line Rated Current	18 A
Product certifications	CSA NEMA UL listed
Control circuit	Control circuit transformer
Provided equipment	2 fuses (primary)
Control type	Selector switch (HAND-OFF-AUTO)
NEMA degree of protection	NEMA 1 painted sheet steel
Rated power in HP	5 HP 575 V AC 5 HP 460 V AC 3 HP 230 V AC 3 HP 200 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	0
Control circuit voltage	480 V AC 60 Hz primary circuit 120 V AC 60 Hz secondary circuit
Local signalling	Red indicator on incandescent
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3

Ordering and shipping details

oraning arra ompleming arotamo	
Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901080633
Nbr. of units in pkg.	1
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be Compliant on 3Q2014	
REACh Reference not containing SVHC above the threshold		

Contractual warranty

,,	Warranty period	18 months
----	-----------------	-----------