Product data sheet Characteristics

TVS3HWA80X HWA TVSS, 240/120, 3 ph, 4 wire, 80kA

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 2810.00 USD



Main

Device short name	HWA	
Provided equipment	Alarm	
Range of product	Surgelogic	

Complementary

Complementary		·
System Voltage	120/240 V AC	
Enclosure material	Plastic	
Local signalling	On normal per phase Off fault per phase	
Mounting location	Service entrance	
Mounting support	Nipple	
Network number of phases	3 phases	
Short-circuit protection	200 kA	
Surge current	<= 80 kA per phase	
Wiring configuration	4-wire	

Environment

NEMA degree of protection	NEMA 4X	
Standards	ANSI/IEEE C62.41 ANSI/IEEE C62.45 UL 1449 : ed. 2 UL 1283 UL Category Section 37.3	

Ordering and shipping details

<u> </u>		
Category	08466 - SURGE PROTECTION HWA	his d
Discount Schedule	DE1B	ner:
GTIN	00785901406204	

his documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1	
Package weight(Lbs)	10.2000000000001	
Returnability	N	
Country of origin MX		
Offer Sustainability		
<u> </u>	Compliant - since 1743 - Schneider Electric declaration of conformity	
Offer Sustainability	Compliant - since 1743 - Schneider Electric declaration of conformity	
Offer Sustainability	_ '	

Contractual warranty

Warranty period 18 months	Contraction warranty			