Product data sheet Characteristics

8536SCT3V06

Non-Reversing Starter Size 1, 3-Pole, Melting Alloy Overload, NEMA 7/9

Stock Code: Non-Stock - Not normally stocked in distribution facility



Price*: 2241.00 USD



Main

Product or component type	Starter	
Range of product	S	
Control circuit	Common control circuit	

Complementary

Complementary		>
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz	— suitability
Motor starter type	Non reversing	_ uiui
[In] rated current	27 A	_ etem_
Poles description	3P	for d
Network number of phases	3 phases	 nsed
Rated power in HP	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	and is not to be
[Ue] rated operational voltage	600 V AC	e for
Control type	No control units) Setitur
Thermal overload type	Melting alloy 3 Thermal Units	a su
Electrical connection	Screw clamp terminals	ed as
NEMA size	1	tende
Height	337 mm	—.i
Depth	178 mm	<u>.s.</u>
Width	279 mm	 entatic

Environment

LITTIONICH	offinent	
NEMA degree of protection	NEMA 7/9 cast iron type: bolted	<u> </u>
Product certifications	CSA	<u>c</u>

Ordering and shipping details

0 11 0	
Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
GTIN	00785901374336
Nbr. of units in pkg.	1
Package weight(Lbs)	19
Returnability	Υ
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014
	Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period 18 months
