

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 2091.00 USD



Main

Product or component type	Starter
Range of product	S
Control circuit	Common control circuit

Complementary

[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Line Rated Current	90 A
Poles description	2P
Phase	2 phases
Rated power in HP	15 HP 230 V AC 7.5 HP 115 V AC
System Voltage	600 V AC
Control type	No control units
Thermal overload type	Melting alloy 2 Thermal Units
Electrical connection	Screw clamp terminals
NEMA size	3
Height	642 mm
Depth	8.62 in (219 mm)
Width	12.83 in (326 mm)

Environment

NEMA degree of protection	NEMA 3R painted sheet steel
Product certifications	UL listed CSA

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901912736
Nbr. of units in pkg.	1
Package weight(Lbs)	27.670000000000002
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------