

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 2124.00 USD



Main

Product or component type	Plug-in unit
Range of product	I-Line
Circuit breaker type	FA
Trip unit technology	Thermal-magnetic

Complementary

Protection type	Circuit breaker
Mounting mode	Plug-in
Line Rated Current	90 A
System Voltage	277/480 V AC
Poles description	3P
Phase	3 phases
Wiring configuration	4-wire (integral ground bus)
Breaking capacity	18 kA at 480 V AC 25 kA at 240 V AC
AWG gauge	AWG 10...AWG 2 1 cable(s) ground AWG 14...AWG 1/0 1 cable(s) phase and neutral
Depth	8.62 in (219 mm)
Height	8.27 in (210 mm)
Width	14.37 in (365 mm)


Environment

Product certifications	UL listed file E22182 CSA C22.2 No 27
Standards	UL 857

Ordering and shipping details

Category	20182 - PFA / PHD C/B PLUGS
Discount Schedule	PE7
GTIN	00785901824862
Nbr. of units in pkg.	1
Package weight(Lbs)	18.5
Returnability	Y
Country of origin	US

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1438 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------