



Price* : 3747.00 USD



Main

Product or component type	Starter
Range of product	S
Control circuit	Separate control circuit

Complementary

[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Line Rated Current	135 A
Poles description	3P
Phase	3 phases
Rated power in HP	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
System Voltage	600 V AC
Control type	No control units
Thermal overload type	Melting alloy 3 Thermal Units
Electrical connection	Screw clamp terminals
NEMA size	4
Height	12.87 in (327 mm)
Depth	6.5 in (165 mm)
Width	5.98 in (152 mm)

Environment

NEMA degree of protection	Not rated (open device)
Product certifications	CSA

NEMA
UL listed

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901924586
Nbr. of units in pkg.	1
Package weight(Lbs)	22
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------