Product data sheet Characteristics

9001KR9P1A PUSHBUTTON OPERATOR 30MM TYPE K +OPTIONS

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 243.00 USD



Main

Main	
Range of product	Harmony 9001K
Product or component type	Mushroom head push-button
Device short name	9001K
Type of operator	Push-pull
Operator profile	Amber mushroom Ø 41 mm unmarked

Complementary

Main		
Range of product	Harmony 9001K	
Product or component type	Mushroom head push-button	
Device short name	9001K	
Type of operator	Push-pull	
Operator profile	Amber mushroom Ø 41 mm unmarked	
Complementary		
Complementary Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
-	0.43 lb(US) (0.195 kg)	
Product weight		
Operating position	Any position	
Shape of signaling unit head	Round	
Head material	Plastic	
Operator position information	2 positions	
Contacts type and composition	Without contact block	
Mechanical durability	5000000 cycles	
Light source	Incandescent	
Bulb base	BA 9s	
Light block supply	Via integral transformer (f = 50/60 Hz) (secondary voltage = 6 V)	
Device presentation	Basic element	
Compatibility code	9001K	
Environment		
Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	

Environment

	,
Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)

Ambient air temperature for operation	-13158 °F (-2570 °C)
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP66 conforming to IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 4 NEMA 6
Standards	CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508
Product certifications	UL 508 NEMA
Vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn conforming to IEC 60068-2-27

Ordering and shipping details

oraning and omplaing and	
Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	00785901034131
Nbr. of units in pkg.	1
Package weight(Lbs)	0.5
Returnability	N
Country of origin	MX

Contractual warranty

Warranty period	18 months