# Product data sheet Characteristics


## 9001SKY303 CONTROL STATION + OPERATORS

Product availability: Non-Stock - Not normally stocked in distribution facility





Price\*: 464.00 USD



#### Main

Range of product	Harmony 9001KY	
Product or component type	Control station	
Device short name	9001KY	
Provided equipment	Label plate with OPEN-CLOSE-STOP marking	
Contact block name	KA1 KA3	
Product specific application	For hoisting and mechanical handling applications	
Level or class	Class III Class II Division 2 Group G	

## Complementary

Enclosure/Cubicle description	Wall-mounted enclosure with 3 cut-outs : Ø 30 mm	:
Enclosure material	Polymeric	
Type of installation	Indoor/Outdoor	:
Control station composition	3 pushbuttons with 2 NO + 3 NC contacts	
Mechanical interlocking	Without mechanical interlock	
Connector type	Screw clamp connector	
Connections - terminals	Direct connection (AWG 2), cable stiffness: solid stranded Direct connection (AWG 12), cable stiffness: solid stranded Direct connection (AWG 24), cable stiffness: solid stranded	
[Ue] rated operational voltage	600 V	-
[le] rated operational current AC	10 A	:

#### **Environment**

ZIIVII OI III IOI I		<u>u</u>
NEMA degree of protection	NEMA 1	E
	NEMA 13	0
	NEMA 3	Ë
	NEMA 4	:. 
Environmental characteristic	Resistant against immersion in water	os Se

## Dust and oil resistant

Product certifications	UL listed
Ambient air temperature for operation	-13140 °F (-2560 °C)
Ambient air temperature for storage	-40158 °F (-4070 °C)

## Ordering and shipping details

Category	21429 - 9001 SK,SKY
Discount Schedule	CS1
GTIN	00785901044642
Nbr. of units in pkg.	1
Package weight(Lbs)	2.5
Returnability	N
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1230 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

### Contractual warranty

Contractual warranty		
Warranty period	18 months	