

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 3623.00 USD



Main

Product or component type	Starter
Range of product	S
Control circuit	Separate control circuit

Complementary

[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Non reversing
Line Rated Current	45 A
Poles description	3P
Phase	3 phases
Rated power in HP	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
System Voltage	600 V AC
Control type	No control units
Thermal overload type	Melting alloy 3 Thermal Units
Electrical connection	Screw clamp terminals
NEMA size	2
Height	702 mm
Depth	10.98 in (279 mm)
Width	13.62 in (346 mm)

Environment

NEMA degree of protection	NEMA 7/9 cast aluminium type: bolted
Product certifications	CSA

NEMA
UL listed

Ordering and shipping details

Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
GTIN	00785901939047
Nbr. of units in pkg.	1
Package weight(Lbs)	50
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------