Product data sheet Characteristics

LA26400AB FA/LA MOLDED CASE CIRCUIT BREAKER, 600V, 400A, 2P, 1PH

Product availability: Stock - Normally stocked in distribution facility





Price*: 4053.00 USD



Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip unit technology	Thermal-magnetic
Breaking capacity code	A

Complementary

Main		
Product or component type	Circuit breaker	
Range of product	I-Line	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	A	
Complementary		
Line Rated Current	400 A	
Poles description	2P	
Breaking capacity	25 kA at 600 V AC 42 kA at 240 V AC	
	30 kA at 480 V AC	
System Voltage	250 V DC	
	600 V AC	
Mounting mode	I-Line	
Electrical connection	I-Line connection line Lugs load	
AWG gauge	AWG 1600 kcmil (aluminium/copper) 1 cable(s) AWG 1250 kcmil (aluminium/copper) 2 cable(s)	
Terminal identifier	AL400LA	
Magnetic hold current	2000 A	
Magnetic tripping current	4000 A	
Wiring configuration	2-wire	
Phase connection	AB	
Height	11 in	
Width	6 in	
Depth	5.84 in	

Environment

Product certifications	CSA
	UL listed

Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901358466
Nbr. of units in pkg.	1
Package weight(Lbs)	15.88000000000001
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Contractual warranty		
Warranty period	18 months	