Product data sheet Characteristics

9001KYK218 CONTROL STATION + OPERATORS

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 329.00 USD



Main

| Device short name | KY | |
|--------------------|---|--|
| Enclosure type | Weatherproof enclosure dust and oil resistant indoor/outdoor | |
| Mounting diameter | 1.18 in (30 mm) | |
| Provided equipment | Contact block 2 KA1 Legend plate 1 KN203 Legend plate 1 KN204 | |

Complementary

| Line Rated Current | 10 A | ō |
|-------------------------------|--|----------|
| Contacts type and composition | 2 NO + 2 NC | Ë |
| Control type | Push-button 1 9001KR1B Push-button 1 9001KR3R | |
| Device mounting | Surface | d |
| Electrical connection | Screw clamp terminal | <u> </u> |
| Enclosure material | Die cast zinc alloy grey | <u> </u> |
| Marking | ON-OFF | 2 |
| Operator profile | 2 projecting push-buttons | |
| Permissible voltage | <= 300 V | Per |
| | | |

Environment

| NEMA degree of protection | NEMA 3/4/13 | |
|---------------------------|--------------------------------|---|
| Product certifications | CE | |
| | CSA LR25490 class 3211 03 | 5 |
| | UL listed file E42259 CCN NKCR | |
| | | |

Ordering and shipping details

| Grading and dinpping ad | orano e e e e e e e e e e e e e e e e e e e | ₽ |
|-------------------------|---|--------|
| Category | 21426 - 9001 K (NOT KA,KM,KX) | ner |
| Discount Schedule | CS1 | clair. |

| GTIN | 00785901039891 |
|-----------------------|----------------|
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 3.73 |
| Returnability | Υ |
| Country of origin | MX |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1230 - Schneider Electric declaration of conformity |
| | Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold |
| | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| Warranty period 18 months |
|---------------------------|
|---------------------------|