

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 1094.00 USD



Main

Product or component type	Starter
Range of product	S
Control circuit	Separate control circuit

Complementary

[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Motor starter type	Reversing
Poles description	2P
Phase	1 phase
Wiring mode	3 wires
Line Rated Current	18 A
Rated power in HP	1 HP 115 V AC 2 HP 230 V AC
System Voltage	600 V AC
Control units	No control units
Thermal overload type	Melting alloy 1 Thermal Units
Electrical connection	Screw clamp terminals
NEMA size	0
Height	11.89 in (302 mm)
Depth	7.52 in (191 mm)
Width	11.89 in (302 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel
Product certifications	CSA

NEMA
UL listed

Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901777816
Nbr. of units in pkg.	1
Package weight(Lbs)	25.210000000000001
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------