

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 5001.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	G

### Complementary

Line Rated Current	250 A
Number of poles	3
Poles description	3P
Breaking capacity	20 kA 250 V DC 65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC 20 kA 500 V DC
System Voltage	500 V DC 600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Terminal nut line Lugs load
AWG gauge	AWG 3/0...350 kcmil aluminium/copper
Magnetic hold current	1250 A
Magnetic tripping current	2500 A
Height	7.52 in
Width	4.12 in
Depth	5 in

### Environment

Product certifications	CCC
------------------------	-----

Feb 24, 2018

CE  
CSA  
IEC  
UL listed

---

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

---

### Ordering and shipping details

---

Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901583370
Nbr. of units in pkg.	1
Package weight(Lbs)	4.8399999999999999
Returnability	Y
Country of origin	US

---

### Offer Sustainability

---

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---