

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 8778.00 USD



Main

Product or component type	Starter
Range of product	S
Control circuit	Common control circuit

Complementary

[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Motor starter type	Non reversing
Line Rated Current	135 A
Poles description	3P
Phase	3 phases
Rated power in HP	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
System Voltage	600 V AC
Control type	No control units
Thermal overload type	Melting alloy 3 Thermal Units
Electrical connection	Screw clamp terminals
NEMA size	4

Environment

NEMA degree of protection	NEMA 7/9 cast aluminium type: bolted
Product certifications	CSA NEMA UL listed

Ordering and shipping details

Category	21202 - 8502,36 S*R,S*T,S*W
Discount Schedule	CP1
GTIN	00785901226673
Nbr. of units in pkg.	1
Package weight(Lbs)	28.400000000000002
Returnability	Y
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------