Product data sheet Characteristics

HGM36150

PowerPact H Circuit Breaker,ThermMagn,150A,3P,600V,18kA

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 3599.00 USD



Main

Product or component type	Circuit breaker	
Range of product	PowerPact H	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	G	

Complementary

Line Rated Current	150 A	
Poles description	3P	<u>.</u>
Breaking capacity	65 kA at 240 V AC 35 kA at 480 V AC 18 kA at 600 V AC 20 kA at 500 V DC 20 kA at 250 V DC	substitute for and is not to be used for rate
System Voltage	250 V DC 500 V DC 600 V AC	io de la companya de
Continuous current rating	80 %	4
Mounting mode	Unit mount	:
Electrical connection	Terminal nut load Lugs line	infanda se
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	
Magnetic hold current	900 A	<u>.</u> <u>.</u>
Magnetic tripping current	1700 A	<u></u> . <u></u>
Height	6.4 in	
Width	4.12 in	- <u> </u>
Depth	4.36 in	ric dycumentation

Environment

Product certifications	CCC CE CSA IEC UL listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Ordorning and oripping dotains	
Category	01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901466826
Nbr. of units in pkg.	1
Package weight(Lbs)	5
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0832 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months	