

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 1062.00 USD



### Main

Control circuit	Separate control circuit
Device short name	S
Enclosure type	Open box

### Complementary

System Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Depth	5.31 in
Electrical connection	Screw terminal
Height	11.52 in
Motor power hp	1 hp 115 V AC 2 hp 230 V AC
Motor starter type	Reversing
Mounting support	Vertical support
NEMA size	0
Network number of phases	1 phase
Number of poles	3
Number of thermal units required	1
Permissible voltage	<= 600 V AC
Product weight	13 lb(US)
Short-circuit protection	5000 A AIR
Thermal overload type	Melting alloy
Width	5.47 in

### Environment

Product certifications	NEMA UL listed
------------------------	-------------------

### Ordering and shipping details

Category	21271 - 8702,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901125495
Nbr. of units in pkg.	1
Package weight(Lbs)	7.9500000000000002
Returnability	N
Country of origin	MX

### Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

### Contractual warranty

Warranty period	18 months
-----------------	-----------