

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 414.00 USD



Main

Device short name	KY
Enclosure type	Weatherproof enclosure dust and oil resistant indoor/outdoor
Mounting diameter	1.18 in (30 mm)
Provided equipment	Legend plate 1 KN202 Contact block 1 KA51

Complementary

Line Rated Current	3 A
Contacts type and composition	1 NO/NC power reed
Control type	Push-button 1 9001KR
Device mounting	Surface
Electrical connection	Screw clamp terminal
Enclosure material	Die cast zinc alloy grey
Marking	STOP
Operator profile	1 projecting push-button
Permissible voltage	<= 300 V

Environment


NEMA degree of protection	NEMA 3/4/13
Product certifications	CE CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR

Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	00785901039877

Nbr. of units in pkg.	1
Package weight(Lbs)	3.1400000000000001
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1230 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------