

# 8538SCA21V81CFF4P92T

## Non-Rever. Combo Starter Size 1, 3P, Melting Alloy Overload, NEMA 12 +Options

Product availability : Non-Stock - Not normally stocked in distribution facility



### Main

Product or component type	Combination Starter
Range of product	S
Control circuit	Control circuit transformer

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz secondary circuit 480 V AC 60 Hz primary circuit
Motor starter type	Non reversing
Line Rated Current	27 A
Poles description	3P
Motor power hp	7.5 hp 230 V AC 3 phases 10 hp 460 V AC 3 phases 10 hp 575 V AC 3 phases 7.5 hp 200 V AC 3 phases
System Voltage	600 V AC
Control type	Selector switch (HAND-OFF-AUTO)
Auxiliary contact composition	Without
Provided equipment	2 fuses primary circuit 1 fuse secondary circuit
Thermal overload type	Melting alloy 3 Thermal Units
Disconnecter device type	Non-fusible disconnect switch
NEMA size	1
Height	24 in
Depth	8.34 in
Width	9.5 in
Length	3.25 in

### Environment

NEMA degree of protection	NEMA 12 painted sheet steel and with external reset
Product certifications	CSA UL listed

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901620662
Nbr. of units in pkg.	1
Package weight(Lbs)	45
Returnability	N