

Product data sheet

Characteristics

8538SCA24V81CFF4H30T

Non-Rever. Combo Starter Size 1, 3P, Motor Logic SSOLR, NEMA 12 +Options

Product availability : Non-Stock - Not normally stocked in distribution facility



Main

Product or component type	Combination Starter
Range of product	S
Control circuit	Control circuit transformer

Complementary

[Uc] control circuit voltage	120 V AC 60 Hz secondary circuit 480 V AC 60 Hz primary circuit
Motor starter type	Non reversing
Line Rated Current	27 A
Poles description	3P
Motor power hp	10 hp 460 V AC 3 phases 10 hp 575 V AC 3 phases
System Voltage	600 V AC
Control type	Selector switch (HAND-OFF-AUTO)
Auxiliary contact composition	Without
Provided equipment	2 fuses primary circuit 1 fuse secondary circuit
Thermal overload type	Solid state Motor Logic class 10/20 9...27 A FLA
Disconnecter device type	Fusible disconnect switch, Type H and K Fuse, 30 A
NEMA size	1
Height	24 in
Depth	8.34 in
Width	9.5 in
Length	3.25 in

Environment

NEMA degree of protection	NEMA 12 painted sheet steel and with external reset
Product certifications	CSA UL listed

Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901703730
Nbr. of units in pkg.	1
Package weight(Lbs)	42.399999999999999
Returnability	N