Product data sheet Characteristics

2510KG2S2

Special Manual Switch - NEMA 1 - 3P - Toggle Operated - No Indicator - 600VAC

Product availability: Stock - Normally stocked in distribution facility



Price*: 166.90 USD



Main

Product or component type	Single Unit Manual Switch
Range of product	К

Complementary

Complementary		-
Line Rated Current	30 A	
Cable entry	0.5" and 0.75" knock-outs (top and bottom)	
Motor power hp	2 hp at 115 V AC 1 hp at 90 V DC 2 hp at 115 V DC 1.5 hp at 230 V DC 7.5 hp at 230 V AC 10 hp at 460 V AC 10 hp at 575 V AC	erbettilia for and is not to be used for datermining suitibility or rail
System Voltage	600 V AC 230 V DC	e is
Poles description	3P	
Control type	Toggle	وً عَلَيْ
Phase	3 phases	Deti:
Local signalling	No indicator	TO TO THE PART OF
Motor starter type	Non reversing	
Electrical connection	Screw clamp terminals	
AWG gauge	AWG 14AWG 10 (copper)	i.
Height	4.25 in	<u>.v</u>
Width	2.44 in	
Depth	2.75 in	in intentation is not intented as

Environment

Product certifications	CF
i ioduci cerinications	ᆫ

UL listed file E42243 CCN NLRV CSA LR25490 class 3211 05

NEMA degree of protection	NEMA 1 plastic standard size	

Ordering and shipping details

Category	21102 - 2510,2511,2512 K		
Discount Schedule	CP1		
GTIN	00785901474593		
Nbr. of units in pkg.	36		
Package weight(Lbs)	0.8000000000000004		
Returnability	Υ		
Country of origin	MX		

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	

Contractual warranty

Warranty period	18 months	