Product data sheet Characteristics

8736SBO1V02S

Reversing Starter Size 0, 2-Pole, Melting Alloy Overload, Horizontal Open +Option

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 1034.00 USD



Main

mann		<u>c</u>
Product or component type	Starter	
Range of product	S	
Control circuit	Separate control circuit	± 2

Complementary

Complementary		
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz	vilisi sinis
Motor starter type	Reversing	
Poles description	2P	
Phase	1 phase	
Wiring mode	3 wires	9
Line Rated Current	18 A	9 2 2
Rated power in HP	1 HP 115 V AC 2 HP 230 V AC	
System Voltage	600 V AC	
Control units	No control units	
Thermal overload type	Melting alloy 1 Thermal Units	enheitina
Electrical connection	Screw clamp terminals	
NEMA size	0	
Height	6.93 in (176 mm)	
Depth	5.31 in (135 mm)	
Width	7.13 in (181 mm)	ia io

Environment

NEMA degree of protection	Not rated (open device)	Ė
Installation direction	Horizontal	- 2

Product certifications	CSA
	NEMA
	UL listed

Ordering and shipping details

21271 - 8702,36 SA,SB(NOT S*R,T,W)
CP1
00785901125471
1
8
N
MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014
	Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months