

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 662.00 USD



Main

Control circuit	Separate control circuit
Device short name	S
Enclosure type	Open box
Product or component type	Motor starter

Complementary

Rated current	36 A
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Depth	4.22 in
Electrical connection	Screw clamp terminal
Height	6.77 in
Motor power hp	3 hp 115 V AC 5 hp 230 V AC
Motor starter type	Non reversing
NEMA size	1P
Network number of phases	1 phase
Number of poles	2
Number of thermal units required	1
Permissible voltage	<= 600 V AC
Product weight	5.5 lb(US)
Thermal overload type	Melting alloy
Width	4.53 in

Environment

Product certifications	CSA UL listed
------------------------	------------------

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901019220
Nbr. of units in pkg.	1
Package weight(Lbs)	5
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------