Product data sheet Characteristics


8536SFO1V07

Non-Reversing Starter Size 4, 3-Pole, Melting Alloy Overload, Open

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 3747.00 USD



Main

TVT CALL		
Product or component type	Starter	_
Range of product	S	
Control circuit	Common control circuit	

Complementary

Complementary		
[Uc] control circuit voltage	600 V AC 60 Hz 550 V AC 50 Hz	6 6 7
Motor starter type	Non reversing	
Line Rated Current	135 A	
Poles description	3P	for o
Phase	3 phases	9
Rated power in HP	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC	and is not to be
System Voltage	600 V AC	
Control type	No control units	
Thermal overload type	Melting alloy 3 Thermal Units	์ เ
Electrical connection	Screw clamp terminals	
NEMA size	4	
Height	12.87 in (327 mm)	i intend
Depth	6.5 in (165 mm)	<u>v</u> .
Width	5.98 in (152 mm)	entation
		<u>y</u>

Environment

- IIII OIIII OIII		F
NEMA degree of protection	Not rated (open device)	
Product certifications	CSA	<u> </u>

Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901609056
Nbr. of units in pkg.	1
Package weight(Lbs)	22
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will not be compliant
	Will not be compliant

Contractual warranty

Warranty period 18 months		
---------------------------	--	--