Product data sheet Characteristics

8536SGG1V06

Non-Reversing Starter Size 5, 3-Pole, Melting Alloy Overload, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 10254.00 USD



Main

Month		<u>(</u>
Product or component type	Starter	-
Range of product	S	
Control circuit	Common control circuit	*

Complementary

Complementary		
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz	
Motor starter type	Non reversing	
Line Rated Current	270 A	
Poles description	3P	-
Phase	3 phases	9
Rated power in HP	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC	is contracting and contracting
System Voltage	600 V AC	
Control type	No control units	######################################
Thermal overload type	Melting alloy 3 Thermal Units	
Electrical connection	Screw clamp terminals	
NEMA size	5	iri Sandad
Height	1123 mm	<u>.</u>
Depth	329 mm	. <u>u</u> .
Width	17.2 in (437 mm)	ta de

Environment

LITTION		\vdash
NEMA degree of protection	NEMA 1 painted sheet steel	mer:
Product certifications	CSA	sclai

Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901854708
Nbr. of units in pkg.	1
Package weight(Lbs)	140
Returnability	Υ
Country of origin	MX

Offer Sustainability

Will not be compliant
Will not be compliant
Reference not containing SVHC above the threshold
Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------