Product data sheet Characteristics

9421V1W30 LOADBREAK SWITCH 600VAC 20A IEC

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 900.50 USD



Main

Color	Red/Yellow
Enclosure type	Water resistant enclosure indoor Dustproof enclosure indoor Corrosion resistance enclosure indoor
Lock type	Padlockable
Range of product	VARIO

Complementary

	46	
6	(I	
Main		
Color	Red/Yellow	
Enclosure type	Water resistant enclosure indoor	
	Dustproof enclosure indoor Corrosion resistance enclosure indoor	
Lock type	Padlockable	
Range of product	VARIO	
Range of product	VANIO	
Complementary		
Line Rated Current	20 A	
Auxiliary contact composition	Without	
Depth	6.25 in	
Device mounting	Surface	
Enclosure material	Stainless steel 304	
Height	7.38 in	
Motor power hp	5 hp at 240 V AC 10 hp at 480/600 V AC	
Permissible voltage	<= 600 V AC	
Width	5.5 in	
Environment		
NEMA degree of protection	NEMA 4/4X	
Product certifications	CSA LR81630 class 3211 05 UL listed file E164864 CCN NLRV CE	
Ordering and shipping details		
Category	21730 - V VARIO SWITCH	
Discount Schedule	CP1	
Cab 24 2040		

Environment

NEMA degree of protection	NEMA 4/4X	
Product certifications	CSA LR81630 class 3211 05	
	UL listed file E164864 CCN NLRV	
	CE	

Ordering and shipping details

Category	21730 - V VARIO SWITCH	
Discount Schedule	CP1	<u></u>

GTIN	00785901909408	
Nbr. of units in pkg.	1	
Package weight(Lbs)	4.66999999999999	
Returnability	N	
Country of origin	MX	
Offer Sustainability		
RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

- Contracted warranty	
Warranty period	18 months