

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 759.00 USD



Main

Color	Red/Yellow
Enclosure type	Dust and damp proof enclosure indoor
Lock type	Padlockable
Range of product	VARIO

Complementary

Line Rated Current	25 A
Auxiliary contact composition	1 NO/1 NC
Depth	6.25 in
Device mounting	Surface
Enclosure material	Metallic metal
Height	7.38 in
Motor power hp	15 hp at 600 V AC 5 hp at 240 V AC 10 hp at 480 V AC
Permissible voltage	<= 600 V AC
Width	5.5 in

Environment

NEMA degree of protection	NEMA 12
Product certifications	CE UL listed file E164864 CCN NLRV CSA LR81630 class 3211 05

Ordering and shipping details

Category	21730 - V VARIO SWITCH
Discount Schedule	CP1

GTIN	00785901058946
Nbr. of units in pkg.	1
Package weight(Lbs)	3.5
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1545 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------