

# TVS3HWA10X

## TVS HWA Surge Protection Device 120/240 V High Leg Delta 3P4W 100 kA

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 3611.00 USD



### Main

Product or component type	Surge protection device
Range of product	Surgelogic
Device short name	HWA

### Complementary

Surge current	100 kA per phase
System Voltage	120/240 V AC
Phase	3 phases
Wiring configuration	4-wire
Connections - terminals	Wire phase and neutral AWG 10 copper Wire ground AWG 10 copper Wire dry contacts AWG 22 copper
[Uc] maximum continuous operating voltage	150 V
Nominal discharge current	20 kA
Number of poles	2
Short-circuit protection	200 kA
Local signalling	Status LED, green = normal operation per phase Status LED, red = fault per phase Alarm = fault
Mounting location	Bottom of enclosure
Device mounting	Surface Flush with fixing kit
Height	4.8 in (122 mm)
Width	8.62 in (219 mm)
Depth	3.11 in (79 mm)


## Environment

NEMA degree of protection	NEMA 4X
Enclosure material	Plastic, colour : black
Standards	CSA C22.2 No 8 1986 UL 1283 ed. 5 UL 1449 ed. 4
Ambient air temperature for operation	149 °F (65 °C)

## Ordering and shipping details

Category	08466 - SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	00785901946434
Nbr. of units in pkg.	1
Package weight(Lbs)	3.8999999999999999
Returnability	N
Country of origin	MX

## Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1743 - Schneider Electric declaration of conformity  <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------