Product data sheet Characteristics

8736SAG16V06

Reversing Starter Size 00, 3-Pole, Melting Alloy Overload, NEMA 1

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 989.00 USD



	Starter	ots.
	S	0
	Common control circuit	
	440 V AC 50 Hz 480 V AC 60 Hz	or reliability of these products (
	Reversing	
	3P	
Phase	3 phases	nii a
Line Rated Current	9 A	
Line Rated Current	1.5 HP 200 V AC 1.5 HP 230 V AC 2 HP 460 V AC 2 HP 575 V AC	is not to be used for determining suitability
System Voltage	600 V AC	
System Voltage	No control units	
System Voltage	Melting alloy 3.0 Thermal Units	
System Voltage	Screw clamp terminals	or of the second
System Voltage	00	substitute for and
System Voltage	11.89 in (302 mm)	
System Voltage	7.52 in (191 mm)	w w
System Voltage	11.89 in (302 mm)	
System Voltage	NEMA 1 painted sheet steel	: :: •
System Voltage	CSA NEMA UL listed	isclaimer: This documentation is not intended as
System Voltage	21271 - 8702,36 SA,SB(NOT S*R,T,W)	
System Voltage	CP1	his d
System Voltage	00785901903628	
System Voltage	1	ni.

System Voltage	23.51000000000002	
System Voltage	N	
System Voltage	MX	
System Voltage	Will be Compliant on 3Q2014	
	Will be Compliant on 3Q2014	
System Voltage	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
System Voltage	18 months	