Product data sheet Characteristics

8536SBW12V03

Non-Reversing Starter Size 0, 3-Pole, Melting Alloy Overload, NEMA 4/4X +Options

Product availability: Non-Stock - Not normally stocked in distribution facility



Price*: 1017.00 USD



Main

Product or component type	Starter	
Range of product	S	
Control circuit	Common control circuit	

Complementary

Complementary		
[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Motor starter type	Non reversing	
Line Rated Current	18 A	
Poles description	3P	7
Phase	3 phases	7
Rated power in HP	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC	.i.
System Voltage	600 V AC	<u>.</u> و
Control type	No control units	**************************************
Thermal overload type	Melting alloy 3 Thermal Units	
Electrical connection	Screw clamp terminals	
NEMA size	0	
Height	13.19 in (335 mm)	
Depth	7.8 in (198 mm)	
Width	6.38 in (162 mm)	

Environment

Enviolment		F
NEMA degree of protection	NEMA 4/4X brushed stainless steel	mer:
Product certifications	UL listed	 scla

Ordering and shipping details

Category	21203 - 8502,36 W/STAINLESS ENCLOSURES
Discount Schedule	CP1
GTIN	00785901057567
Nbr. of units in pkg.	1
Package weight(Lbs)	33.1000000000001
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Will be compliant on 3Q2014
	Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------