

Product data sheet

Characteristics

HJL36100U33X

PowerPact H Circuit Breaker, Micrologic 3.2S, 100A, 3P, 600V, 25kA

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 2444.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip unit technology	Electronic standard Micrologic 3.2 S LSI
Breaking capacity code	J

Complementary

Line Rated Current	100 A
Poles description	3P
Breaking capacity	65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC
System Voltage	600 V AC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 14...AWG 3/0 (aluminium/copper)
Height	6.4 in
Width	4.12 in
Depth	4.36 in

Environment

Product certifications	CCC CE CSA IEC UL listed
------------------------	--------------------------------------

Ambient air temperature for operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	01107 - H/J ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
GTIN	00785901852476
Nbr. of units in pkg.	1
Package weight(Lbs)	5
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------