

# Product data sheet

## Characteristics

# DTU322

## SWITCH NOT FUSIBLE DT N1 240V 60A 3P



Product availability: Stock - Normally stocked in distribution facility

### Main

Product	Double Throw Safety Switch
Line Rated Current	60 A
Certifications	UL listed
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	None
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
System Voltage	240 V AC 250 V DC
Wire Size	AWG 12...AWG 2 (aluminium) AWG 14...AWG 2 (copper)

### Complementary

Width	11.96 in
Height	29.94 in
Depth	6.93 in
Tightening torque	40 lbf.in (AWG 8) 40 lbf.in for 8.37 mm <sup>2</sup> (AWG 8) 45 lbf.in for 13.3...21.15 mm <sup>2</sup> (AWG 6...AWG 4) 50 lbf.in for 26.67...33.62 mm <sup>2</sup> (AWG 3...AWG 2) 35 lbf.in for 2.06...5.26 mm <sup>2</sup> (AWG 14...AWG 10)

### Ordering and shipping details

Category	00133 - DT SWITCH,NEMA3R
Discount Schedule	DE1
GTIN	00785901308362
Nbr. of units in pkg.	1
Package weight(Lbs)	35.240000000000002
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including:
----- Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
----- More information	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------