

# Product data sheet

## Characteristics

# 8910DPA63V09

8910DPA definite purpose contactor, 60 Amp, 3 P, 220/208 to 240 V 50/60 Hz coil, open

Product availability: Stock - Normally stocked in distribution facility



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	60 A
Number of Poles	3P
Pole contact composition	3 NO
Range of product	DPA

### Complementary

Maximum Horse Power Rating	5 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 30 Hp 460 V AC, 3 phases 30 Hp 575 V AC, 3 phases 25 hp 230 V AC, 3 phases
Locked rotor rated current	360 A 277 V AC 300 A 460 V AC 240 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	3 phases
Electrical connection	Box lugs Quick connect terminals

### Environment

Product certifications	UL listed CSA
------------------------	------------------

### Ordering and shipping details

Category	21346 - 8910 DPA 6_(60 AMP)
Discount Schedule	CP1B
GTIN	00785901080794
Package weight(Lbs)	0.68 kg (1.5 lb(US))
Returnability	Yes
Country of origin	CN

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Under investigation
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty

18 months

---