LX1D6W6

TeSys D - contactor coil - LX1D6 - 277 V AC 60 Hz for 80 & 95 A contactor

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Range	TeSys
Product or component type	Contactor coil
Device short name	LX1D6
Control circuit type	AC 60 Hz
[Uc] control circuit voltage	277 V AC 60 Hz
Average resistance	157 Ohm 68 °F (20 °C)
Inductance of closed circuit	8 H
Product compatibility	LC1D95 LC1D80
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits Drop-out 0.30.6 Uc 50/60 Hz 131 °F (55 °C)) Operational 0.81.1 Uc 50 Hz 131 °F (55 °C)) Operational 0.851.1 Uc 60 Hz 131 °F (55 °C))		
Inrush power in VA	220 VA 60 Hz 0.75 68 °F (20 °C))	
Hold-in power consumption in VA	22 VA 60 Hz 0.3 68 °F (20 °C))	
Heat dissipation	610 W 50/60 Hz	

Environment

Ambient air temperature for operation	23140 °F (-560 °C)
Net weight	0.62 lb(US) (0.28 kg)

Ordering and shipping details

22341 - CONTACTOR,D,K,&F ACCESS	
l12	
00785901441694	
0.34 kg (0.74 lb(US))	
No	
CZ	
	00785901441694 0.34 kg (0.74 lb(US)) No

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide	
	& Antimony trioxide which is known to the State of California to cause Carcinogen	
	harm. For more information go to www.p65warnings.ca.gov	

Contractual warranty

Warranty	18 months	