



Main

Product	Adaptor
Range	I-Line

Complementary

Rated Current	800 A copper
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	304.80 mm (12 in)
Material	Copper busbar
I-LINE Value End	Slot
Number of Phases	3 phase
For Use with	Busbar trunking 800 A copper
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire
Mounting Location	Indoor

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	20029-800A CU FEEDER BUS IP54 THERMAL
Discount Schedule	PE8
GTIN	00785901084747
Package weight(Lbs)	19.20 lb(US) (8.709 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------