

Product data sheet

Characteristics

8903SVA11V02

lighting contactor, mechanically held, 200 A, 2 pole, NEMA 12, 120/110V 60/50Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product	Mechanically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	200 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	41.50 in (1054 mm)
Depth	10.24 in (260 mm)
Width	22.17 in (563 mm)

Environment

Enclosure Type	NEMA 12/3R painted sheet steel surface none
Product certifications	UL listed CSA

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901781325
Package weight(Lbs)	4.42 kg (9.75 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------