

# Product data sheet

## Characteristics

# QO12040M200RB125

QO LoadCenter, Main Breaker, 200A, 125A  
MB, 1PH-3W, 20SP, NEMA 3R

Product availability: Non-Stock - Not normally stocked in distribution facility



## Main

Product	Load Center
Marketing Trade Name	QO
Cover type	Surface cover

## Complementary

Load Center Type	Main breaker
Line Rated Current	125 A
Number of spaces	20
Short Circuit Current Rating	22 kA
Maximum Number of Single Pole Circuits	40
Maximum Number of Tandem Breakers	20
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 4...250 kcmil aluminium/copper
Electrical Connection	Lugs
Grounding Bar	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Busbar Material	Tin plated copper busbar
Enclosure Material	Welded galvanized steel
Cover Finish	Baked enamel grey
Box number	5R
Height	26.02 in (661 mm)
Width	14.76 in (375 mm)

## Environment

Enclosure Rating	NEMA 3R outdoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL listed

## Ordering and shipping details

Category	00002 - QO 1PH LC,12-42 CKT,NEMA3R
Discount Schedule	DE3A
GTIN	00785901684442
Package weight(Lbs)	13.64 kg (30.08 lb(US))
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Will be compliant – Date to be confirmed

Contractual warranty

Warranty	18 months
----------	-----------