

Product data sheet

Characteristics

8903SPG2V06

lighting contactor, electrically held, 60 A, 3 pole, NEMA 1, 480/440V 60/50Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Current Rating	60 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	12.68 in (322 mm)
Depth	6.02 in (153 mm)
Width	7.80 in (198 mm)

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product certifications	UL listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901160113
Package weight(Lbs)	5.01 kg (11.05 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------