## Product data sheet Characteristics

# 9007MS06S0206

9007MS limit switch - top push plunger - bushing mount - 6' side cable

Product availability: Non-Stock - Not normally stocked in distribution facility



| Main                      |                  |
|---------------------------|------------------|
| Range of product          | 9007             |
| Series name               | Miniature potted |
| Product or component type | Limit switch     |
| Device short name         | 9007MS/ML        |
| Sensor design             | Miniature        |
| Body type                 | Fixed            |
| Head type                 | Plunger head     |
| Material                  | Metal            |
| Body material             | Cast zinc        |
| Number of poles           | 1                |

#### Complementary

| 1  |   |
|--|---|
| Fixing mode                                  | By the head   |
| Movement of operating head                   | Linear  |
| Type of operator                             | Spring return plunger stainless steel bushing mounted   |
| Type of approach                             | Vertical approach, 1 direction  |
| Switch actuation                             | On end  |
| Contacts type and composition                | NC-NO   |
| Switch function                              | SPDT  |
| Contact form                                 | Form C  |
| Contacts material                            | Silver contacts   |
| Contact operation                            | Snap action   |
| Positive opening                             | Without   |
| Electrical connection                        | Pre-wired cable side  |
| Type of cable                                | SJTO AWG 18), 1.83 m (6 ft), yellow   |
| Terminals description ISO n°1                | (Green-yellow)Gnd<br>(Black)Com<br>(White)NO<br>(red)NC   |
| Wire insulation material                     | PVC   |
| Maximum force for tripping                   | 80 ozf  |
| [le] rated operational current               | 6 A 120 V AC, A300 NEMA rating designation<br>3 A 240 V AC, A300 NEMA rating designation<br>5 A 28 V DC |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 300 V 3)UL 508<br>300 V 3)CSA C22.2 No 14   |
| Electrical durability                        | 100000 cycles   |
| Mechanical durability                        | 10000000 cycles   |
| Marking                                      | CSA<br>CE<br>UL   |
| Sale per indivisible quantity                | 1   |
| Height                                       | 44.45 mm (1.75 in)  |
| Width  | 39.62 mm (1.56 in)  |
| Depth  | 15.75 mm (0.62 in)  |
| Product weight                               | 0.54 kg (1.2 lb(US))  |
|  |   |

#### Environment

| Shock resistance                      | 35 gn 9 ms IEC 60068-2-27   |
|---------------------------------------|---|
| Vibration resistance                  | 10 gn 751200 Hz)IEC 60529   |
| NEMA degree of protection             | NEMA 1 Nema type 250<br>NEMA 2 Nema type 250<br>NEMA 4 Nema type 250<br>NEMA 6 Nema type 250<br>NEMA 6P Nema type 250 |
| IP degree of protection               | IP67 IEC 60529  |
| Ambient air temperature for operation | -40104 °C (-40220 °F)   |
| Ambient air temperature for storage   | -40104 °C (-40220 °F)   |
| Protective treatment                  | Epoxy powder coat   |
| Product certifications                | UL<br>CE<br>CSA   |
| Standards                             | E78403<br>LR 25490 Class 32 11 03   |
|                                       |   |

### Ordering and shipping details

| Category            | 22431 - LIMIT SWITCHES,TYPE 9007MS |
|---------------------|------------------------------------|
| Discount Schedule   | DS1                                |
| GTIN                | 00785901121350                     |
| Package weight(Lbs) | 0.54 kg (1.2 lb(US))               |
| Returnability       | No                                 |
| Country of origin   | MX                                 |

## Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
|---------------------------|--|
| REACh Regulation          | REACh Declaration  |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope   |
| Environmental Disclosure  | Product Environmental Profile  |
| Circularity Profile       | No need of specific recycling operations   |

## Contractual warranty

| Warranty 18 months |
|--------------------|
|--------------------|