

Main

Product or Component Type	Elbow
Range	I-Line



Complementary

Rated Current	3000 A
Busbar Material	Copper busbar
Busbar Position	Edgewise
Integral Ground	50 percent capacity integral ground bus High short-circuit bracing
Rated Operational Voltage	600 V AC
Number of Phases	3 phase
Wiring Configuration	4-wire
Length	279.40 mm (11 in)
Height	279.40 mm (11 in)

Ordering and shipping details

Category	20043-3000A/3200A CU FEEDER BUS IP54 THER
Discount Schedule	PE8
GTIN	00785901275626
Package weight(Lbs)	115.96 lb(US) (52.599 kg)
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------