

# Product data sheet

## Characteristics

# 8903SMG60V02

combo lighting, electrically held, 3P, 30A, no fuse, NEMA 1, 120/110V 60/50Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



## Main

Product	Combination electrically held lighting contactor
Type	S

## Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnecter device type	Non-fusible disconnect switch
Electrical connection	Lugs
Height	22.52 in (572 mm)
Depth	8.39 in (213 mm)
Width	9.49 in (241 mm)

## Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product certifications	UL listed file E16151 CCN NRNT

## Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901482925
Package weight(Lbs)	12.63 kg (27.85 lb(US))
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------