HOM20L125C LOAD CENTER HOM MLO 240V 125A 1PH 20SP



Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Product or component type	Load Center
Marketing Trade Name	Homeline
Load center type	Main lugs
Line Rated Current	125 A
Number of spaces	20
Number of circuits	20
Enclosure Rating	NEMA 1 indoor
Cover type	Combination flush/surface cover

Lugs

Comp	piem	enta	ary
Chart	oiroui	t our	ont

Short-circuit current	10 kA
Number of Tandem Breakers	0
Number of Phases	1 phase
[Ue] rated operational voltage	120/240 V AC
Wire Size	AWG 6AWG 2/0 aluminium AWG 6AWG 2/0 copper
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Busbar Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	8
Height	26.02 in (661 mm)
Width	14.21 in (361 mm)
Depth	3.74 in (95 mm)
Tightening torque	5.65 N.m (50 lbf.in) AWG 6AWG 2/0)

Electrical connection

Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)	
Product certifications	UL E-6294	

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901061250
Package weight(Lbs)	10.92 kg (24.08 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	Lifetime
----------	----------