

# Product data sheet

## Characteristics

# 8903SMW2V02C

lighting contactor, electrically held, 30 A, 3 pole, NEMA 4/4X, 120/110V 60/50Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



## Main

Product	Electrically Held Lighting Contactor
Type	S

## Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	Selector switch 3 positions HAND-OFF-AUTO)
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	13.19 in (335 mm)
Depth	7.13 in (181 mm)
Width	6.38 in (162 mm)

## Environment

Enclosure Type	NEMA 4/4X brushed stainless steel surface none
Product certifications	UL listed CSA

## Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901533443
Package weight(Lbs)	16.77 kg (36.97 lb(US))
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------