QO320L100GNYC

QO LoadCenter, Main Lug, 100A, 3PH, 20 SP, NEMA 1, NYC Special Current Density



Main

Product	Lo	ad Center
Marketing Tr	ade Name QC)
Cover type	Or	der separately

Complementary

Complementary	
Load Center Type	Main lugs
Line Rated Current	100 A
Number of spaces	20
Short Circuit Current Rating	65 kA
Maximum Number of Single Pole Circuits	20
Maximum Number of Tandem Breakers	0
Number of Phases	3 phase
Wire Size	AWG 4AWG 2/0 aluminium/copper
Grounding Bar	Grounding bar included (not installed)
Electrical connection	Lugs
Wiring configuration	4-wire 3-wire
Busbar Material	Tin plated copper busbar
Enclosure Material	Welded sheet steel
Cover Finish	Baked enamel grey
Box number	7
Height	20.91 in (531 mm)
Width	14.25 in (362 mm)
Depth	37.36 in (949 mm)
Tightening torque	5.65 N.m (50 lbf.in) AWG 6AWG 1)

Environment

Enclosure Rating	NEMA 1 indoor
Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL listed

Ordering and shipping details

Category	00011-QO 3PH LOAD CENTER,INDOOR
Discount Schedule	DE3
GTIN	00785901295051
Package weight(Lbs)	12.86 lb(US) (5.833 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Will be compliant – Date to be confirmed
Contractual warranty	
Warranty	18 months